

SMART THERMAL KIOSK

Meets FDA guidelines

INSTANT RESULTS IN 1-2 SECONDS



ATTENDANCE TRACKING AND TEMPERATURE MEASUREMENT



**MASK
DETECTION**



**FACIAL
RECOGNITION**



**BUILT-IN NFC
SWIPE CARDREADER**



**MEASURE DISTANCE
4" - 13"**



**HIGH TEMPERATURE
ALERT**



**AUTOMATIC
ATTENDANCE TRACKING**



**HEALTH QUESTIONS
SUPPORT**



**SUPPORT
6 LANGUAGES**



BADGE PRINTER SUPPORT



PDF/EXCEL REPORTS



SMART THERMAL KIOSK

COMMERCIAL GRADE SCREENING SYSTEM

- Good for high traffic areas, like schools, factories, warehouses, offices, stores. Much faster than hand-held temperature gun.
- Collects answers to health questions before scanning with state-of-the-art touchless pad. Questions are customizable.
- Works with DYMO printer to print name tags for each scan with pass/fail and date.
- Supports multi-location & rooms, web-based administration, pdf & excel reports per location or combined.
- Records all users temperature & time of scan via facial recognition or RFID scan (ID Badge swipe) in the cloud.
- Privacy mode can be enabled to store only Pass/Fail instead of temperature for maximum privacy requirements.
- Sends email & SMS alerts for high & abnormal temperature or absence of mask.

MODEL: FG- STD-10AN

TECHNICAL SPECS	CPU: QUAD CORE 1.2GHZ. GPU: MAIL400 MP2, ANDROID 7.1, 1GB RAM, 8GB STORAGE
SCREEN SIZE	10.2" IPS, 1280X800 ANTI-GLARE TEMPERED GLASS SCREEN
DIMENSIONS & WEIGHT	L 15"X W 9.4" - NET 3.3 LB, GROSS 4.4 LB
THERMAL SENSORS	OMRON MEMS + ENV. THERMOMETER PLATINUM RESISTANCE TEMPERATURE DETECTOR - ACCURACY ±0.3°C (1°F)
OTHER SENSORS	OPTICAL(200 MP HD CAMERA), DISTANCE (LASER, 940NM LASER)
SPEAKER	BUILT-IN 10W SPEAKER, EXTERNAL SPEAKER CONNECTION AVAILABLE
PORTS	1 X DC POWER IN, 1 X 3.5MM AUDIO OUT, 1 X MICRO SD CARD SLOT, 2 X USB PORTS, 1 X RJ45 LAN
NFC/RFID	NXP MFRC522, SUPPORT ISO/IEC 14443A/ MIFARE® CARDS
POWER ADAPTER	INCLUDED - AC 110-220V / OUTPUT DC12V -2A, CONSUMPTION 12W, NO INTERNAL BATTERY
VESA MOUNTING	75 X 75 MM (3" X 3")

